13	
١Ū	
ΙĎ	
13	
i≟	
H	•
	<b>V</b> )
	N
S	C
	9

1	1. A method comprising:
2	determining a portion of a codestream to edit;
3	decoding the portion of the codestream;
4	performing an edit to the decoded portion of the codestream;
5	recompressing edited data into coded data; and
6	generating a replacement portion for the portion of the codestream by
7	making size of the replacement portion equal to size of the portion of the
8	codestream by adding padding to the replacement tile if the replacement tile
9	is smaller than the portion of the codesteam or quantizing the replacement
10	tile/if the replacement tile is larger than the portion of the codestream.

2. The method defined in Claim 1 wherein quantizing the replacement tile comprises truncating packets in the replacement tile until the size of the replacement tile is equal to the size of the portion of the

codestream.

1

The method defined in Claim 1 wherein creating a replacement 1 2 tile includes providing an indication in the replacement tile that other 3 portions of the codestream contain useless data. The method defined in Claim 3 wherein the other portions of 4. 1 the codestream comprises tile-parts in the codestream subsequent to the 2 3 portion of the codestream. The method defined in Claim 1 wherein the portion comprises 5. 1 2 at least one of a group including: a tile, a tile-part, or packet. 1 6. The method defined in Claim 1 wherein the portion covers at 2 least one of a/group that include an area, a resolution, a component, and a 3 precinct. An article of manufacture comprising at least one recordable 1 2 media \$toring executable instructions thereon which, when executed by a 3 processing device, cause the processing device to:

determine a portion of a codestream to edit;

	ū		
	П		
	ļ		
	M	$\mathcal{L}$	
( )	ifi	- 1	
$\setminus I$	***		
X	气	4/	1
Y		<b>Y</b>	1
Y		₹! !	1
YE C		\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	1
YE C		<u> </u>	<b>1</b>
7		\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	<b>1</b>
Ye C		<u> </u>	<b>1</b>
YE .		<i>\\'</i>	1 ا

5	decode the portion of the codestream;
6	perform an edit to the decoded portion of the codestream;
7	recompress edited data into coded data; and
8	generate a replacement portion for the portion of the codestream by
9	making size of the replacement portion equal to size of the portion of the
10	codestream by adding padding to the replacement tile if the replacement tile
11	is smaller than the portion of the codesteam or quantizing the replacement
12	tile if the replacement tile is larger than the portion of the codestream.
<b>→</b>	8. An apparatus comprising:
2	determining a portion of a codestream to edit;
3	means for decoding the portion of the codestream;
4	means for performing an edit to the decoded portion of the
5	codestream;
6	means for recompressing edited data into coded data; and
7	neans for generating a replacement portion for the portion of the
8	codes ream by making size of the replacement portion equal to size of the
9	portion of the codestream by adding padding to the replacement tile if the
10	replacement tile is smaller than the portion of the codesteam or quantizing

codestream.

11 the replacement tile if the replacement tile is larger than the portion of the 12 codestream. 1 9. A method comprising: determining a portion of a codestream to edit; 2 3 decoding the portion of the codestream; performing an edit to the decoded portion of the codestream; 4 5 recompressing edited data into coded data; and 6 generating a replacement portion for the portion of the codestream by 7 making size of the replacement portion equal to size of the portion of the 8 codestream/by using a marker of an appropriate length if the replacement 9 tile is smaller than the portion of the codesteam or quantizing the 10 replacement tile if the replacement tile is larger than the portion of the 11 codestream. 1 10. The method defined in Claim 9 wherein quantizing the 2 replacement tile comprises truncating packets in the replacement tile until 3 the size of the replacement tile is equal to the size of the portion of the

- 1 The method defined in Claim 9 wherein creating a replacement
- 2 tile includes providing an indication in the replacement tile that other
- 3 portions of the codestream contain useless data.
- 1 12. The method defined in Claim 11 wherein the other portions of
- 2 the codestream comprises tile-parts in the codestream subsequent to the
- 3 portion of the codestream.
- 1 13. The method defined in Claim 9 wherein the portion comprises
- 2 at least one of a group including: a tile, a tile-part, or packet.
- 1 14./ The method defined in Claim 9 wherein the portion covers at
- 2 least one of a group that include an area, a resolution, a component, and a
- 3 precipct.

- 15. The method defined in Claim 9 wherein the marker comprises
- 2 a COM marker of the JPEG 2000 Standard.

1	16. An article of manufacture comprising at least one recordable
2	media storing executable instructions thereon which, when executed by a
3	processing device, cause the processing device to:
4	determine a portion of a codestream to edit;
5	decode the portion of the codestream;
6	perform an edit to the decoded portion of the codestream;
7	recompress edited data into coded data; and
8	generate a replacement portion for the portion of the codestream by
9	making size of the replacement portion equal to size of the portion of the
10	codestream by using a marker of an appropriate length if the replacement
11	tile is smaller than the portion of the codesteam or quantizing the
12	replacement tile if the replacement tile is larger than the portion of the
13	codestream.
1	7. A method comprising:
2	means for determining a portion of a codestream to edit;
3	means for decoding the portion of the codestream;
4	means for performing an edit to the decoded portion of the
5	codestream;

6	means for recompressing edited data into coded data; and
7	means for generating a replacement portion for the portion of the
8	codestream by making size of the replacement portion equal to size of the
9	portion of the codestream by using a marker of an appropriate length if the
10	replacement tile is smaller than the portion of the codesteam or quantizing
11	the replacement tile if the replacement tile is larger than the portion of the
12	codestream.
1	18. A method comprising:
12	determining a portion of a codestream to edit;
3	decoding the portion of the codestream;
4	performing an edit to the decoded portion of the codestream;
5	recompressing edited data into coded data, including placing coded
6	data at an end of a codestream file and replacing useless data in a marker.
1	19. The method defined in Claim 18 wherein the marker comprises
2 /	a C <del>OM mar</del> ker.

pagnand namen

1	-20. An article of manufacture comprising at least one recordable
2	media storing executable instructions thereon which, when executed by a
3	processing device, cause the processing device to:
4	determine a portion of a codestream to edit;
5	decode the portion of the codestream;
6	perform an edit to the decoded portion of the codestream;
7	recompress edited data into coded data, including placing coded data
8	at an end of a codestream file and replacing useless data in a marker.
•	
1	21. / A method comprising:
2	means for determining a portion of a codestream to edit;
3	means for decoding the portion of the codestream;
4	means for performing an edit to the decoded portion of the
5	codestream;
6	means for recompressing edited data into coded data, including
7	placing coded data at an end of a codestream file and replacing useless data
8	in a marker.

00%